



PRO-PLOW® Series 2 Specifications

Technical Specifications

Imperial	7' 6" MS	8' MS	8' 6" MS	7' 6" POLY	8' POLY
Blade Width	7' 6"	8'	8' 6"	7' 6"	8'
Blade Height	29"	29"	29"	29"	29"
Blade Gauge	11	11	11	3/8" Poly	3/8" Poly
Trip Springs	4	4	4	4	4
Shock Absorbers	1	1	1	1	1
Vertical Ribs	7	7	7	7	7
Lift Cylinder	1 1/2" x 8"	1 1/2" x 8"	1 1/2" x 8"	1 1/2" x 8"	1 1/2" x 8"
Angling Rams	1 1/2" x 10"	1 1/2" x 10"	1 1/2" x 10"	1 1/2" x 10"	1 1/2" x 10"
Plowing Width (Full Angle)	6' 6"	6' 11"	7' 4"	6' 6"	6' 11"
Approx. Weight*	653 lb	668 lb	686 lb	677 lb	690 lb
Disc Shoes	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron
Cutting Edge	3/8" x 6"	3/8" x 6"	3/8" x 6"	3/8" x 6"	3/8" x 6"
Mount Type	UltraMount® 2	UltraMount® 2	UltraMount® 2	UltraMount® 2	UltraMount® 2

Metric	7' 6" MS	8' MS	8' 6" MS	7' 6" POLY	8' POLY
Blade Width	2.29 m	2.44 m	2.59 m	2.29 m	2.44 m
Blade Height	73.66 cm	73.66 cm	73.66 cm	73.66 cm	73.66 cm
Blade Gauge	3.18 mm	3.18 mm	3.18 mm	9.52 mm	9.52 mm
Trip Springs	4	4	4	4	4
Shock Absorbers	1	1	1	1	1
Vertical Ribs	7	7	7	7	7
Lift Cylinder	3.81 cm x 20.32 cm	3.81 cm x 20.32 cm	3.81 cm x 20.32 cm	3.81 cm x 20.32 cm	3.81 cm x 20.32 cm
Angling Rams	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm
Plowing Width (Full Angle)	1.98 m	2.11 m	2.24 m	1.98 m	2.11 m
Approx. Weight*	296 kg	302 kg	311 kg	307 kg	312 kg
Disc Shoes	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron
Cutting Edge	0.95 cm x 15.24 cm	0.95 cm x 15.24 cm	0.95 cm x 15.24 cm	0.95 cm x 15.24 cm	0.95 cm x 15.24 cm
Mount Type	UltraMount® 2	UltraMount® 2	UltraMount® 2	UltraMount® 2	UltraMount® 2