

SNOWPLOW SPECIFICATIONS



XLS™ Series



XtremeV™



HD Series



XBLADE™



MC Series



HT Series™



SD Series



Model	Blade Width	Blade Height	Blade Gauge	Trip Springs	Ribs	Angling Rams	Plowing Width (full angle)	Approx. Weight complete	Wear Shoes (cast iron)	Standard Cutting Edge	Optional Cutting Edge
HT Series™	7'6"	27"	14	2	6+Tube	1-1/2" x 8"	6'7"	414#	optional	-	3/8" x 6" steel 1/2" x 6" steel 1" x 6" poly
SD Series	6'9"	26"	14	2	8	1 1/2" x 10"	6'1"	472#	optional	1" x 6" Poly	-
SD Series	7'6"	26"	14	2	8	1 1/2" x 10"	6'9"	487#	optional	1" x 6" Poly	-
HD Series	7' 6"	29"	12	3	8	1 1/2" x 12"	6'7"	630#	standard	-	3/8" x 6" or 1/2" x 6"
HD Series	8'	29"	11	4	8	1 1/2" x 12"	7'1"	717#	standard	-	1/2" x 6"
HD Series	8'6"	29"	11	4	8	1 1/2" x 12"	7'6"	731#	standard	-	1/2" x 6"
HD Series	9'	29"	11	4	8	1 1/2" x 12"	7'11"	745#	standard	-	1/2" x 6"
XBLADE™	7'6"	31"	14	4	10	1 1/2" x 12"	6'7"	742#	optional	-	1/2" x 6"
XBLADE	8'	31"	12*	4	10	1 1/2" x 12"	7'1"	790#	optional	-	1/2" x 6"
XBLADE	8'6"	31"	12	4	10	1 1/2" x 12"	7'6"	813#	optional	-	1/2" x 6"
XBLADE	9'	31"	12*	4	10	1 1/2" x 12"	7'11"	835#	optional	-	1/2" x 6"
Plus Vehicle Mount – average 60#											
* Available with stainless steel or 1/4" Polyethylene moldboards											
MC Series	9'	34"	11	4	8	2" x 16"	7'11"	1350#	standard	1/2" x 8"	-
MC Series	10'	34"	11	6	8	2" x 16"	8'10"	1428#	standard	1/2" x 8"	-
Plus Vehicle Mount – average 184#											

Model	Blade Width	Blade Height @ Blade End	Height @ Hinge	Blade Gauge	Number of Springs	Ribs	Angling Rams	Plowing Width @ Full Angle	Plowing Width @ Scoop	Plowing Width @ Full V	Cutting Edge	Off-Truck Weight W/Blade	Wear Shoes (cast iron)
XtremeV™ PC	7'6"	30 3/4"	29"	12	4	12	1 3/4" x 11"	6'6"	6'3"	6'9"	3/8" x 6"	821#	optional
XtremeV SS	7'6"	30 3/4"	29"	12	4	12	1 3/4" x 11"	6'6"	6'3"	6'9"	3/8" x 6"	821#	optional
XtremeV PC	8'6"	31"	29"	12	4	12	1 3/4" x 11"	7'5"	7'1"	7'7"	3/8" x 6"	876#	optional
XtremeV SS	8'6"	31"	29"	12	4	12	1 3/4" x 11"	7'5"	7'1"	7'7"	3/8" x 6"	876#	optional
XtremeV PC	9'6"	33"	31"	12	6	12	1 3/4" x 11"	8'3"	7'11"	8'7"	1/2" x 6"	1005#	optional
XtremeV SS	9'6"	33"	31"	12	6	12	1 3/4" x 11"	8'3"	7'11"	8'7"	1/2" x 6"	1005#	optional
PC–Powder Coated Steel SS–Stainless Steel													

Model	Blade Width (Retracted)	Blade Width (Extended)	Blade Width (Scoop)	Blade Width @ Full Angle	Blade Height	Blade/Wing Gauge	Cutting Edge (Optional)	Wing Cutting Edge Material	Ribs	Trip Springs	Angling Rams	Blade Shoes	*Plow Weight
XLS™	96" (8')	120" (10')	106" (8'-10")	86"/108"/95"	29"	12 ga/12ga	1/2" x 6" Top Punched	1 1/2" x 9" Polyurethane	Blade Center-6 Full; 2 half Blade Wings-1 Full (Each Wing)	4 Compression	1 1/2" x 10"	optional	985#
*Plus Vehicle Mount–average 60#													



Fisher Engineering reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used. Fisher Engineering or the vehicle manufacturer may require or recommend optional vehicle equipment for snow removal. Do not exceed vehicle ratings with a snowplow.

This product is manufactured under the following US patents: 4,999,935; 5,353,530; 5,420,480; 5,638,618; 5,899,007; 6,253,470; 6,408,549; 6,944,978; 7,400,048; 7,430,821; RE35,700; CAN patents 2,060,425; 2,184,922; 2,229,783; 2,356,036; and other patents pending.

Fisher Engineering offers a limited warranty on all snowplows and accessories. See separately printed page for this important information. The following are registered (®); or unregistered (™) trademarks of Douglas Dynamics, L.L.C.: EZ-V®, FISHER®, Fish-Stik®, HT Series™, INTENSIFIRE™, Minute Mount®, Minute Mount® 2, PRO-CASTER™, ProTube™, SECURITY GUARD™, SnoFoil®, STORM GUARD™, XBLADE™, XLS™, XtremeV™.

FISHER ENGINEERING • 50 GORDON DRIVE • ROCKLAND, MAINE 04841 • www.fisherplows.com